



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

1. Identification of the Substance / Preparation and of the Company / Undertaking

Product identifier

Product Name Winter-eez RV & Marine -50 °F Burst Antifreeze

Stock Numbers 142001 / 142002 / 142005

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use RV & Marine Antifreeze

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name South/Win, Ltd
Supplier Address 112 Maxfield Rd.
Greensboro, NC 27405
US

Supplier Phone Number Phone: (800) 648-4393
Fax: (336) 398-5680

Emergency Telephone Number CHEMTREC: (800) 424-9300

2. Hazards Identification

Emergency Overview

Color: Red
Physical State: Liquid
Odor: mild, sweet

Hazards of product:

No significant immediate hazards for emergency response are known.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Health Effects

Eye Contact: May cause slight temporary eye irritation. Corneal injury is unlikely.

Skin Contact: Prolonged exposure not likely to cause significant skin irritation. Repeated contact may cause flaking and softening of skin.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Inhalation: At room temperature, exposure to vapor is minimal due to low volatility. Mist may cause irritation of upper respiratory tract (nose and throat).

Ingestion: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Aspiration hazard: Based on physical properties, not likely to be an aspiration hazard.

Effects of Repeated Exposure: In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

3. Composition / Information on Ingredients

Component	CAS #	Amount
Propylene glycol	57-55-6	> 12.0 - < 20.0%
Glycerol	56-81-5	> 12.0 - < 20.0%
Dipotassium hydrogen phosphate	7758-11-4	> .50 - < 2.0%
Water	7732-18-5	> 60.0 - < 80.0%

4. First Aid Measures

Eye Contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Skin Contact: Wash skin with plenty of water.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Ingestion: No emergency medical treatment necessary.

Notes to Physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Emergency Personnel Protection: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

5. Fire-fighting Measures

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

6. Accidental Release Measures

Steps to be taken if Material is Released or Spilled:

Small spills: Absorb with materials such as: Cat litter. Sawdust. Vermiculite. Zorb-all®. Collect in suitable and properly labeled containers.

Large spills: Dike area to contain spill. See Section 13, Disposal Considerations, for additional information.

Personal Precautions: Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: No special precautions required. Keep container closed. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Storage: Store in a dry place. Do not store in: Galvanized steel. Opened or unlabeled containers. Store in the following material(s): Carbon steel. Stainless steel. Store in original unopened container. See Section 10 for more specific information. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

8. Exposure Controls / Personal Protection

Exposure Limits



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

Component	List	Type	Value
Propylene glycol	WEEL	TWA Aerosol	10 mg/m ³
Glycerol	ACGIH	TWA Mist	10 mg/m ³
	OSHA Table	PEL	5 mg/m ³
	Z-1	Respirable fraction	
	OSHA Table	PEL Total	15 mg/m ³
	Z-1	dust	

Personal Protection

Eye/Face Protection: Use safety glasses (with side shields).

Skin Protection: Wear clean, body-covering clothing.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

9. Physical and Chemical Properties

Physical State	Liquid.
Color	Red
Odor	mild, sweet
Odor Threshold	No test data available
Flash Point - Closed Cup	104 °C (219 °F) <i>Pensky-Martens Closed Cup ASTM D 93</i> (based on major component), Propylene glycol.
Flammability (solid,gas)	Not applicable to liquids
Flammable Limits In Air	
Lower:	2.6 %(V) <i>Literature</i> Propylene glycol.
Upper:	12.5 %(V) <i>Literature</i> Propylene glycol.
Autoignition Temperature	371 °C (700 °F) <i>Literature</i> Propylene glycol.
Vapor Pressure	2.0 mmHg <i>Literature</i>
Boiling Point (760mmHg)	166 °C (331 °F) <i>Calculated</i> .
Vapor Density (air = 1)	>1.0 <i>Literature</i>
Specific Gravity (H2O = 1)	1.08 - 1.15 20 °C/20 °C <i>Literature</i>
Freezing Point	supercools
Melting Point	Not applicable to liquids
Solubility in water (by weight)	100 % <i>Literature</i>
pH	10.0 (@ 50 %) <i>Measured</i>
Decomposition Temperature	No test data available
Partition coefficient, n-octanol/water (log Pow)	No data available for this product.
Evaporation Rate(Butyl Acetate = 1)	<0.5 <i>Estimated</i> .
Kinematic Viscosity	88 - 190 cSt @ 20 °C <i>Literature</i>

10. Stability and Reactivity

Stable under recommended storage conditions. See Storage, Section 7.

Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Avoid moisture. Avoid direct sunlight or ultraviolet sources.

Incompatible Materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous Polymerization: Will not occur.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers. Organic acids.

11. Toxicological Information

Acute Toxicity

Ingestion	Based on information for component(s): Rat > 17,000 mg/kg
Dermal	Based on information for component(s): Rabbit > 10,000 mg/kg
Inhalation	As product. The LC50 has not been determined.
Eye damage/eye irritation	May cause slight temporary eye irritation. Corneal injury is unlikely.
Skin corrosion/irritation	Prolonged exposure not likely to cause significant skin irritation. Repeated contact may cause flaking and softening of skin.

Sensitization

Skin	For the major component(s): Did not cause allergic skin reactions when tested in humans.
Respiratory	No relevant information found.
Repeated Dose Toxicity	In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

Chronic Toxicity and Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

Developmental Toxicity	Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.
Reproductive Toxicity	For the major component(s): In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.
Genetic Toxicology	Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

12. Ecological Information

ENVIRONMENTAL FATE

Data for Component: Propylene glycol

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is very high (Koc between 0 and 50). Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Henry's Law Constant (H): 1.2E-08 atm*m3/mole Measured
 Partition coefficient, n-octanol/water (log Pow): -0.92 Measured
 Partition coefficient, soil organic carbon/water (Koc): < 1 Estimated.

Persistence and Degradability

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Biodegradation may occur under anaerobic conditions (in the absence of oxygen).

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
1.28E-11 cm ³ /s	10 h	Estimated

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
81%	28 d	OECD 301F Test
96 %	64 d	OECD 306 Test

Biological oxygen demand (BOD):

BOD 5	BOD 10	BOD 20	BOD 28
69%	70%	86%	

Chemical Oxygen Demand: 1.53 mg/mg
 Theoretical Oxygen Demand: 1.68 mg/mg



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

Data for Component: Glycerol

Movement & Partitioning Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is very high (Koc between 0 and 50). Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Henry's Law Constant (H): 1.73E-08 atm*m3/mole; 25 °C Measured

Partition coefficient, n-octanol/water (log Pow): -1.76 Measured

Partition coefficient, soil organic carbon/water (Koc): 1 Estimated.

Persistence and Degradability

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
63 %	14 d	OECD 301C Test

Theoretical Oxygen Demand: 1.22 mg/mg

Data for Component: Dipotassium hydrogen phosphate

Movement & Partitioning No bioconcentration is expected because of the relatively high water solubility.

Persistence and Degradability: Biodegradation is not applicable.

ECOTOXICITY

Data for Component: Propylene glycol

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (*Oncorhynchus mykiss*), 96 h: 44,000 - 51,600 mg/l

Aquatic Invertebrate Acute Toxicity



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

EC50, water flea Daphnia magna, 48 h, immobilization: 4,850 - 34,000 mg/l

Aquatic Plant Toxicity

EC50, green alga Pseudokirchneriella subcapitata (formerly known as Selenastrum capricornutum), biomass growth inhibition, 96 h: 19,000 mg/l

Toxicity to Micro-organisms

EC50; bacteria, Growth inhibition, 16 h: 26,000 mg/l

EC50, OECD 209 Test; activated sludge, respiration inhibition, 3 h: > 1,000 mg/l

Data for Component: Glycerol

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, fathead minnow (Pimephales promelas), static, 96 h: 44,000 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea Daphnia magna, 24 h: > 10,000 mg/l

Toxicity to Micro-organisms

EC50, OECD 209 Test; activated sludge, respiration inhibition, 3 h: > 1,000 mg/l

Data for Component: Dipotassium hydrogen phosphate

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, golden orfe (Leuciscus idus), static, 48 h: > 900 mg/l

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information.

FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

14. Transport Information

DOT Non-Bulk
NOT REGULATED

DOT Bulk
NOT REGULATED

IMDG
NOT REGULATED

ICAO/IATA
NOT REGULATED

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	No
Delayed (Chronic) Health Hazard	No
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

<u>Component</u>	<u>CAS #</u>	<u>Amount</u>
Propylene glycol	57-55-6	> 12.0 - < 20.0%
Glycerol	56-81-5	> 12.0 - < 20.0%

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances

List: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

Toxic Substances Control Act (TSCA)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. Other Information

Hazard Rating System

NFPA	Health	Fire	Reactivity
	0	1	0

Recommended Uses and Restrictions

Intended as a plumbing antifreeze for Recreational Vehicles. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

Revision

Identification Number: 1017082 / 0000 / Issue Date 06/29/2010 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit



Safety Data Sheet

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9170

TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for Activities such as exposure monitoring and medical surveillance if exceeded.

Prepared By: Randy Boitz

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.